

1N-35
345723

Report 11157
June 1998

GENCORP
AEROJET

**Integrated Advanced Microwave Sounding Unit-A
(AMSU-A)**

Performance Verification Report

METSAT 3 A2 Assembly, Serial Number 107

AMSU-A2 Antenna Assembly, P/N 1331210-3-SPN, S/N 03

**Contract No. NAS 5-32314
CDRL 208**

Submitted to:

**National Aeronautics and Space Administration
Goddard Space Flight Center
Greenbelt, Maryland 20771**

Submitted by:

**Aerojet
1100 West Hollyvale Street
Azusa, California 91702**

Aerojet

**Integrated Advanced Microwave Sounding Unit-A
(AMSU-A)
Verification Test Report
METSAT 3 A2 Assembly
Serial Number 107**

**TEST ITEM: AMSU-A2 ANTENNA ASSEMBLY
P/N 1331210-3-SPN
SERIAL NUMBER 03**

Submitted To:

**National Aeronautics and Space Administration
Goddard Space Flight Center
Greenbelt, Maryland 20771**

Submitted By:

**Aerojet
1100 West Hollyvale Street
Azusa, California 91702**

AMSU-A2 VERIFICATION TEST REPORT

Test Item: AMSU-A2 Antenna Assembly, P/N 1331210-3-SPN
S/N F03

Level of Assembly: Subassembly


Type Hardware: Antenna Assembly

Verification
Procedure No. AE-26002/4J

Initial Test: Start Date: 5/27/98

Applicable
Verification Plan: Verification Plan, Report No. 10360

Facility
Description: AESD Compact Antenna Range


Test Engineer

6/04/98
Date

1.0 SUMMARY

The Flight Model AMSU-A2 Antenna Assembly, P/N 1331210-3, was acceptance tested per AES Test Procedure AE-26002/4J. The tests included beamwidth, beam pointing, beam efficiency and a comprehensive set of antenna patterns as required in Paragraph 6.2.6 of the AMSU-A Performance and Operation Specification, S-480-80.

The AMSU-A2 Antenna Assembly satisfactorily passed all requirements of the S-480-80 specification.

During beam pointing tests, the window channel means for beam positions 1 and 15 exceeded the allowable limit of $0.0^\circ \pm 0.2^\circ$. The reflector assembly, P/N 1355835-1, S/N 06, was replaced with the next available reflector assembly, S/N 07. Beam pointing tests were repeated and the reflector satisfactorily met all requirements.

2.0 REASON FOR TEST

The Acceptance Test Procedure, AE-26002/4J, consists of tests designed to show compliance of the antenna assemblies with Paragraphs 3.7 and 6.2.6 of the S-480-80 specification. The tests reported herein demonstrate the acceptability of the AMSU-A antenna assemblies.

3.0 ABSTRACTS, CONCLUSIONS AND RECOMMENDATIONS

Abstracts containing descriptions of analyses used to derive beam pointing angle, beam efficiency and antenna return loss from measured data are provided in Section 3.4 of the AE-26002/4J test procedure.

4.0 RESULTS OF TESTS

The results of the tests required in AES Test Procedure AE-26002/4J are presented in the following section as test data. As shown on the test data sheets the measured data passed all requirements.

5.0 TEST DATA

Test data for the AMSU-A2 antenna assembly is attached. The data sheet number, type of tests and antenna-under-test is shown in Table 1. Also attached is a complete set of principal plane, co-polar antenna patterns for the AMSU-A2 unit.

TABLE 1

DATA SHEET	TEST	ANTENNA
5	Derivation of Window Channel Mean	A2
16	Laser Alignment System Verification	A2
18	Dynamic Range/Amplitude Accuracy Test	A2
19	Beamwidth Test	A2
20	Crosstrack Alignment	A2
21	Downtrack Alignment	A2
23	Beam Efficiency Test	A2

TEST DATA SHEET 5
Derivation of Window Channel Mean (A1 and A2)

A1-1 or A1-2

Frequency (GHz) (± 0.1)	Beam Position 1		Beam Position 15		Beam Position 30	
	Cross Track (Deg)	Down Track (Deg)	Cross Track (Deg)	Down Track (Deg)	Cross Track (Deg)	Down Track (Deg)
50.3 (Ch 3)	<i>Not Required for A1 Testing</i>					
52.8 (Ch 4)						
89.0 (Ch 15)						
Computed Mean*						
Required Mean	N/A	0.0° ± 0.2°	N/A	0.0° ± 0.2°	N/A	0.0° ± 0.2°
Pass/Fail	N/A		N/A		N/A	

5-30.9.
QC
236

A2

Frequency (GHz) (± 0.1)	Beam Position 1		Beam Position 15		Beam Position 30	
	Cross Track (Deg)	Down Track (Deg)	Cross Track (Deg)	Down Track (Deg)	Cross Track (Deg)	Down Track (Deg)
23.8 (Ch 1)	48.40	+1.14	1.71	+1.19	-48.29	+1.11
31.4 (Ch 2)	48.41	+1.12	1.69	+1.09	-48.33	+1.03
Computed Mean*	48.41	+1.13	1.70	+1.14	-48.31	+1.07
Required Mean	N/A	0.0° ± 0.2°	N/A	0.0° ± 0.2°	N/A	0.0° ± 0.2°
Pass/Fail	N/A	P	N/A	P	N/A	P

* Mean is defined as:

$$\text{Mean} = \frac{\text{Max Angle} - \text{Min Angle}}{2} + \text{Min Angle}$$

These test partially satisfy the requirements of S-480-80 paragraphs 3.7.1 and 3.7.3.4.

Check procedure paragraph that applies:

3.4.1.3, 3.4.2.3, 3.4.3.3 (X) RF
3.4.4.3, 3.4.5.3, 3.4.6.3 () IF

Assembly No. 133 1210-3

Serial No. F03

Customer R. Brown 6/6/98

Engineer Luis G. Landa

Quality Assurance AM Chavez 5/29/98

Date 5/29/98

6 Apr 98

TEST DATA SHEET 16
Dynamic Range/Amplitude Accuracy Test (A2)

Laser Alignment System Verification

	Required	Measured	Pass/Fail
Crosstrack Mean	≤ 0.02	0.02	P
Downtrack Mean	≤ 0.02	0.02	P

Frequency GHz (± 0.1)	Dynamic Range (dB)		Amplitude Accuracy (dB)		Pass/Fail
	Required	Measured	Required	Measured	
31.40	Required ≤ -50	Measured -50	Required ≤ -86	Measured -86	

RF Engineering Model Only

Wm G. Hand
 5/29/98
 (236)
 QC 236
 5-30-98

These tests satisfy the requirements of S-480-80 paragraph 6.2.6.2.

Check procedure paragraph that applies: 3.4.3.2 (X) RF
 3.4.6.2 () IF

Assembly No. 1331210-3

Serial No. F03

Customer R. Brown 6/2/98

Engineer Wm G. Hand
 Quality Assurance At Chavira 5/30/98
 Date 5/29/98

TEST DATA SHEET 17
Beamwidth Test (A2)

Frequency GHz (± 0.1)	Beam Position	Nominal Beamwidth (degrees)					
		Tolerance		Measured			Pass/Fail
		Mini- mum	Maxi- mum	Downtrack	Crosstrack	Average	
23.80	1	2.97	3.63	3.53	3.52	3.53	P
	15			3.50	3.49	3.50	P
	30			3.49	3.55	3.52	P
31.40	1	2.97	3.63	3.39	3.39	3.39	P
	15			3.47	3.21	3.34	P
	30			3.39	3.30	3.35	P

Channel-to-Channel Variance		
Parameter	Measured (degrees)	Pass/Fail
Maximum Ave BW	3.53	N/A
Minimum Ave BW	3.34	N/A
Max-Min	0.19	P
Tolerance	$\leq 0.33^\circ$	N/A

Pass = P
Fail = F

These tests partially satisfy the requirements of S-480-80 paragraph 3.7.1 and 3.7.3.4.

Check procedure paragraph that applies: 3.4.3.3 (X) RF
3.4.6.3 () IF

Assembly No. 1331210-3

Serial No. F03

Customer R. Brown 6/2/98

Engineer [Signature]

Quality Assurance [Signature] 5/30/98

Date 5/29/98

6 Apr 98

TEST DATA SHEET 18
Crosstrack Alignment Test (A2)

Frequency GHz (± 0.1)	Beam Position	Tolerance (degrees)			Measured (degrees)	Pass/Fail
		Nominal	Low Limit*	Up Limit*		
23.80	1	48.33	48.21	48.61	48.40	P
	15	1.66	1.50	1.90	1.71	P
	30	-48.33	-48.51	-48.11	-48.29	P
31.40	1	48.33	48.21	48.61	48.41	P
	15	1.66	1.50	1.90	1.69	P
	30	-48.33	-48.51	-48.11	-48.33	P

* The tolerance limits are defined as:
 Upper limit = Window channel mean + 0.2°
 Lower limit = Window channel mean - 0.2°
 Where window channel mean is derived from TDS 5.

These tests partially satisfy the requirements of S-480-80 paragraphs 3.7.1 and 3.7.3.4.

Check procedure paragraph that applies: 3.4.3.3 ☒ RF
 3.4.6.3 ☐ IF

Assembly No. 1331210-3

Serial No. F03

Customer 12. Power 6/2/98

Engineer D. G. Gaud

Quality Assurance 5/29/98

Date 5/29/98

TEST DATA SHEET 19
Downtrack Alignment Test (A2)

Frequency (GHz) (± 0.1)	Beam Position	Tolerance (degrees)			Measured (degrees)	Pass/Fail
		Nominal	Low Limit*	Up Limit*		
23.80	1	0.0	-0.07	+0.33	+0.14	P
	15	0.0	-0.06	+0.34	+0.19	P
	30	0.0	-0.13	+0.27	+0.11	P
31.40	1	0.0	-0.07	+0.33	+0.12	P
	15	0.0	-0.06	+0.34	+0.09	P
	30	0.0	-0.13	+0.27	+0.03	P

* The tolerance limits are defined as:
 Upper limit = Window channel mean + 0.2°
 Lower limit = Window channel mean - 0.2°
 Where window channel mean is derived from TDS 5.

These tests partially satisfy the requirements of S-480-80 paragraphs 3.7.1 and 3.7.3.4.

Check procedure paragraph that applies: 3.4.3.3 (x) RF
 3.4.6.3 () IF

Assembly No. 1331210-3
 Serial No. F03
 Customer R. Brown 6/2/98

Engineer [Signature]
 Quality Assurance [Signature]
 Date 5/29/98

29 May 1998

16:23:45

DATAFILE: AH264

ANGULAR POSITION: .12 DEGREES
HALF-POWER BEAMWIDTH: 3.39 DEGREES

BP1

31.4 GHz

D.T.

DATAFILE: AH266

ANGULAR POSITION: .09 DEGREES
HALF-POWER BEAMWIDTH: 3.47 DEGREES

BP15

DATAFILE: AH268

ANGULAR POSITION: .03 DEGREES
HALF-POWER BEAMWIDTH: 3.39 DEGREES

BP30

PN: 1331210-3

SO: 335305

SN: F03

DP: 0078

T.E.: D. R. S.

QA: J. A. Chavira 5/29/98

DLMC: R. R. R. 6/2/98

DATE: 5/29/98

29 May 1998

16:22:23

DATAFILE: AH263

ANGULAR POSITION: 48.41 DEGREES
HALF-POWER BEAMWIDTH: 3.39 DEGREES

BP1

31.4 GHz
C.T.

DATAFILE: AH265

ANGULAR POSITION: 1.69 DEGREES
HALF-POWER BEAMWIDTH: 3.21 DEGREES

BP15

DATAFILE: AH267

ANGULAR POSITION: -48.33 DEGREES
HALF-POWER BEAMWIDTH: 3.3 DEGREES

BP30

PN: 1331210-3

SC: 335305

SN: F03

OP: 0078

TE: [Signature]

QA: [Signature] 5/30/98

DCMC: R. P. [Signature] 6/6/98

DATE: 5/29/98

29 May 1998

16:24:42

DATAFILE: AH273

ANGULAR POSITION: 48.4 DEGREES
HALF-POWER BEAMWIDTH: 3.52 DEGREES

BP1

23.8 GHz

C.T.

DATAFILE: AH271

ANGULAR POSITION: 1.71 DEGREES
HALF-POWER BEAMWIDTH: 3.49 DEGREES

BP15

DATAFILE: AH269

ANGULAR POSITION: -48.29 DEGREES
HALF-POWER BEAMWIDTH: 3.55 DEGREES

BP30

PN: 1331210-3

SO: 335305

SN: F03

OP: 0078

TE: D. D. A.

QA: J. M. Churn 5/30/98

DCMC: R. Brown 6/2/98

DATE: 5/29/98

6 Apr 98

TEST DATA SHEET 20
Beam Efficiency Test (A2)

Fre- quency (GHz) (±0.1)	Beam Position	DATA FILES								Required Beam Efficiency (%)	Measured Beam Efficiency (%)	Pass/ Fail
		0 Degree Plane		45 Degree Plane		90 Degree Plane		135 Degree Plane				
		Co-Pol	X-Pol	Co-Pol	X-Pol	Co-Pol	X-Pol	Co-Pol	X-Pol			
23.8	1	AH275	AH276	AH277	AH278	AH279	AH280	AH281	AH282	≥ 95%	96 %	PASS
	15	AH283	AH284	AH285	AH286	AH287	AH288	AH289	AH290	≥ 95%	96 %	PASS
	30	AH291	AH292	AH293	AH294	AH295	AH296	AH297	AH298	≥ 95%	96 %	PASS
	COLD CAL	AH323	AH324			AH325	AH326			N/A	N/A	N/A
31.40	1	AH315	AH316	AH317	AH318	AH319	AH320	AH321	AH322	≥ 95%	97 %	PASS
	15	AH307	AH308	AH309	AH310	AH311	AH312	AH313	AH314	≥ 95%	97 %	PASS
	30	AH299	AH300	AH301	AH302	AH303	AH304	AH305	AH306	≥ 95%	97 %	PASS

These tests partially satisfy the requirements of S-480-80 paragraphs 3.7.2, 3.7.4, and 6.2.6.

Check procedure paragraph that applies:

3.4.3.5 ☒ RF
3.4.6.5 () IF

Assembly No. 1331210-3

Serial No. F03

Customer R. Brown 6/6/98

Engineer [Signature]

Quality Assurance [Signature]

Date 6/2/98

1 Jun 1998 08:32:36
PHI=0 IS THE SYMMETRICAL PLANE
DATA IS INTEGRATED ACROSS THE MAINBEAM

23.8GHz

BPI

DATAFILE

INTEGRATION LIMITS

PHI ANGLE	PRIN POL	CROSS POL	LOWER	UPPER	PEAK
0	AH275	AH276	-4.40	+4.40	+0.00
45	AH277	AH278	-4.40	+4.40	-.13
90	AH279	AH280	-4.40	+4.20	-.12
135	AH281	AH282	-4.20	+4.40	+0.04

TOTAL POWER:

SUM PRIN FOR 1 IS .07477
SUM PRIN FOR 2 IS .07538
SUM PRIN FOR 3 IS .07482
SUM PRIN FOR 4 IS .07294
SUM PRINCIPAL TOTAL POWER IS: .29791

SUM CROSS FOR 1 IS .00385
SUM CROSS FOR 2 IS .00219
SUM CROSS FOR 3 IS .00052
SUM CROSS FOR 4 IS .00176
SUM CROSS TOTAL POWER IS: .00833

SUM TOTAL POWER IS: .30624

BEAM POWER:

SUM PRIN FOR 1 IS .07320 3.52 8.80
SUM PRIN FOR 2 IS .07343 3.48 8.70
SUM PRIN FOR 3 IS .07193 3.47 8.68
SUM PRIN FOR 4 IS .07083 3.41 8.53
BEAM PRIN POWER IS: .28939

SUM CROSS FOR 1 IS .00255
SUM CROSS FOR 2 IS .00107
SUM CROSS FOR 3 IS .00001
SUM CROSS FOR 4 IS .00105
SUM CROSS TOTAL POWER IS: .00468

SUM BEAM POWER IS: .29407

BEAM EFFICIENCY IS: 96.00 %

PN: 1331210-3

SN: F03

SO: 335305

OP: 0078

TE: [Signature]

QA: [Signature]

DCMC: R. Brown 6/2/98

DATE: 6/2/98

1 Jun 1998 08:34:37
PHI=0 IS THE SYMMETRICAL PLANE
DATA IS INTEGRATED ACROSS THE MAINBEAM

23.8 GHz

BP15

DATAFILE			INTEGRATION LIMITS		
PHI ANGLE	PRIN POL	CROSS POL	LOWER	UPPER	PEAK
0	AH283	AH284	-4.40	+4.40	+.11
45	AH285	AH286	-4.40	+4.40	-.12
90	AH287	AH288	-4.20	+4.40	+.17
135	AH289	AH290	-4.40	+4.20	-.09

TOTAL POWER:

SUM PRIN FOR 1 IS .07581
SUM PRIN FOR 2 IS .07398
SUM PRIN FOR 3 IS .07592
SUM PRIN FOR 4 IS .07277
SUM PRINCIPAL TOTAL POWER IS: .29848

SUM CROSS FOR 1 IS .00327
SUM CROSS FOR 2 IS .00163
SUM CROSS FOR 3 IS .00033
SUM CROSS FOR 4 IS .00258
SUM CROSS TOTAL POWER IS: .00780

SUM TOTAL POWER IS: .30627

BEAM POWER:

SUM PRIN FOR 1 IS .07428 3.55 8.88
SUM PRIN FOR 2 IS .07240 3.50 8.75
SUM PRIN FOR 3 IS .07219 3.44 8.60
SUM PRIN FOR 4 IS .07077 3.43 8.58
BEAM PRIN POWER IS: .28963

SUM CROSS FOR 1 IS .00233
SUM CROSS FOR 2 IS .00109
SUM CROSS FOR 3 IS .00001
SUM CROSS FOR 4 IS .00135
SUM CROSS TOTAL POWER IS: .00477

SUM BEAM POWER IS: .29440

BEAM EFFICIENCY IS: 96.00 %

PN: 1331210-3

SN: F03

SO: 335305

OP: 0078

TE: JDZ

QA: [Signature]

DCMC: R. Brown 6/6/98

DATE: 6/2/98

1 Jun 1998 11:47:54
PHI=0 IS THE SYMMETRICAL PLANE
DATA IS INTEGRATED ACROSS THE MAINBEAM

23.8 GHz
BP 30

DATAFILE			INTEGRATION LIMITS		
PHI ANGLE	PRIN POL	CROSS POL	LOWER	UPPER	PEAK
0	AH291	AH292	-4.40	+4.00	-.19
45	AH293	AH294	-4.20	+4.40	+.06
90	AH295	AH296	-4.20	+4.40	+.02
135	AH297	AH298	-4.40	+4.20	+.02

TOTAL POWER:

SUM PRIN FOR 1 IS .07309
SUM PRIN FOR 2 IS .07431
SUM PRIN FOR 3 IS .07398
SUM PRIN FOR 4 IS .07442
SUM PRINCIPAL TOTAL POWER IS: .29579

SUM CROSS FOR 1 IS .00296
SUM CROSS FOR 2 IS .00170
SUM CROSS FOR 3 IS .00047
SUM CROSS FOR 4 IS .00200
SUM CROSS TOTAL POWER IS: .00712

SUM TOTAL POWER IS: .30292

BEAM POWER:

SUM PRIN FOR 1 IS .07139 3.39 8.48
SUM PRIN FOR 2 IS .07233 3.46 8.65
SUM PRIN FOR 3 IS .07126 3.41 8.53
SUM PRIN FOR 4 IS .07196 3.46 8.65
BEAM PRIN POWER IS: .28693

SUM CROSS FOR 1 IS .00196
SUM CROSS FOR 2 IS .00111
SUM CROSS FOR 3 IS .00003
SUM CROSS FOR 4 IS .00122
SUM CROSS TOTAL POWER IS: .00431

SUM BEAM POWER IS: .29125

BEAM EFFICIENCY IS: 96.00 %

PN: 1331210-3

SN: F03

SO: 335305

OP: 0078

TE: [Signature]

QA: [Signature]

DCMC: [Signature] 6/2/98

DATE: 6/2/98

2 Jun 1998 12:20:56
PHI=0 IS THE SYMMETRICAL PLANE
DATA IS INTEGRATED ACROSS THE MAINBEAM

31.4 GHz
BP1

DATAFILE			INTEGRATION LIMITS		
PHI ANGLE	PRIN POL	CROSS POL	LOWER	UPPER	PEAK
0	AH315	AH316	-4.40	+4.60	+0.00
45	AH317	AH318	-4.40	+4.60	+0.08
90	AH319	AH320	-4.40	+4.60	+0.06
135	AH321	AH322	-4.60	+4.60	-.07

TOTAL POWER:

SUM PRIN FOR 1 IS .07651
SUM PRIN FOR 2 IS .07780
SUM PRIN FOR 3 IS .07922
SUM PRIN FOR 4 IS .07954
SUM PRINCIPAL TOTAL POWER IS: .31308

SUM CROSS FOR 1 IS .00296
SUM CROSS FOR 2 IS .00203
SUM CROSS FOR 3 IS .00080
SUM CROSS FOR 4 IS .00129
SUM CROSS TOTAL POWER IS: .00708

SUM TOTAL POWER IS: .32016

BEAM POWER:

SUM PRIN FOR 1 IS .07580 3.58 8.95
SUM PRIN FOR 2 IS .07625 3.56 8.90
SUM PRIN FOR 3 IS .07713 3.60 9.00
SUM PRIN FOR 4 IS .07794 3.65 9.13
BEAM PRIN POWER IS: .30712

SUM CROSS FOR 1 IS .00227
SUM CROSS FOR 2 IS .00121
SUM CROSS FOR 3 IS .00037
SUM CROSS FOR 4 IS .00090
SUM CROSS TOTAL POWER IS: .00475

SUM BEAM POWER IS: .31187

BEAM EFFICIENCY IS: 97.00 %

PN: 1331210-3

SN: F03

SO: 335305

OP: 0078

TE: T. D. R. O.

QA: [Signature]

DCMC: [Signature]

DATE: 6/2/98

1 Jun 1998 17:01:08
PHI=0 IS THE SYMMETRICAL PLANE
DATA IS INTEGRATED ACROSS THE MAINBEAM

31.4 GHz
BPIS

DATAFILE			INTEGRATION LIMITS		
PHI ANGLE	PRIN POL	CROSS POL	LOWER	UPPER	PEAK
0	AH307	AH308	-4.40	+4.20	-.14
45	AH309	AH310	-4.40	+4.40	-.10
90	AH311	AH312	-4.60	+4.60	+0.00
135	AH313	AH314	-4.60	+4.40	-.06

TOTAL POWER:

SUM PRIN FOR 1 IS .07529
SUM PRIN FOR 2 IS .07601
SUM PRIN FOR 3 IS .08153
SUM PRIN FOR 4 IS .07755
SUM PRINCIPAL TOTAL POWER IS: .31038

SUM CROSS FOR 1 IS .00228
SUM CROSS FOR 2 IS .00198
SUM CROSS FOR 3 IS .00022
SUM CROSS FOR 4 IS .00241
SUM CROSS TOTAL POWER IS: .00689

SUM TOTAL POWER IS: .31727

BEAM POWER:

SUM PRIN FOR 1 IS .07340 3.42 8.55
SUM PRIN FOR 2 IS .07473 3.51 8.78
SUM PRIN FOR 3 IS .07914 3.67 9.18
SUM PRIN FOR 4 IS .07601 3.57 8.93
BEAM PRIN POWER IS: .30328

SUM CROSS FOR 1 IS .00168
SUM CROSS FOR 2 IS .00149
SUM CROSS FOR 3 IS .00001
SUM CROSS FOR 4 IS .00163
SUM CROSS TOTAL POWER IS: .00481

SUM BEAM POWER IS: .30809

BEAM EFFICIENCY IS: 97.00 %

PN: 1331210-3

SN: F03

SO: 335305

OP: 0078

TE: J. J. 256

QA: [Signature]

DCMC: R. R. 16/6/98

DATE: 4/2/98

1 Jun 1998 14:35:20
PHI=0 IS THE SYMMETRICAL PLANE
DATA IS INTEGRATED ACROSS THE MAINBEAM

31.4 GHz
BP30

DATAFILE			INTEGRATION LIMITS		
PHI ANGLE	PRIN POL	CROSS POL	LOWER	UPPER	PEAK
0	AH299	AH300	-4.40	+4.40	-.05
45	AH301	AH302	-4.40	+4.80	+.12
90	AH303	AH304	-4.60	+4.40	-.02
135	AH305	AH306	-4.20	+4.40	+.12

TOTAL POWER:

SUM PRIN FOR 1 IS .07573
SUM PRIN FOR 2 IS .08030
SUM PRIN FOR 3 IS .07951
SUM PRIN FOR 4 IS .07662
SUM PRINCIPAL TOTAL POWER IS: .31217

SUM CROSS FOR 1 IS .00319
SUM CROSS FOR 2 IS .00129
SUM CROSS FOR 3 IS .00080
SUM CROSS FOR 4 IS .00195
SUM CROSS TOTAL POWER IS: .00722

SUM TOTAL POWER IS: .31939

BEAM POWER:

SUM PRIN FOR 1 IS .07492 3.54 8.85
SUM PRIN FOR 2 IS .07887 3.68 9.20
SUM PRIN FOR 3 IS .07741 3.59 8.98
SUM PRIN FOR 4 IS .07414 3.44 8.60
BEAM PRIN POWER IS: .30534

SUM CROSS FOR 1 IS .00231
SUM CROSS FOR 2 IS .00100
SUM CROSS FOR 3 IS .00028
SUM CROSS FOR 4 IS .00129
SUM CROSS TOTAL POWER IS: .00488

SUM BEAM POWER IS: .31022

BEAM EFFICIENCY IS: 97.00 %

PN: 1331210-3

SN: F03

SD: 335305


OP: 0078

TE: [Signature]

QA: [Signature]


DCMC: 6/2/98 D. Ruen

DATE: 6/2/98




METSAT 2 A2, 23.8 GHZ
BEAM POS. 1, CROSSTRACK PLANE
DATAFILE (S): AH275

DATE: 30 May 1998




METSAT 2 A2, 23.8 GHZ
BEAM POS. 1, DOWNTRACK PLANE
DATAFILE (S): AH279

DATE: 30 May 1998




METSAT 2 A2, 23.8 GHZ
BEAM POS. 15, CROSSTRACK PLANE
DATAFILE (S): AH283

DATE: 30 May 1998




METSAT 2 A2, 23.8 GHZ
BEAM POS. 15, DOWNTRACK PLANE
DATAFILE (S): AH287

DATE: 1 Jun 1998




METSAT 2 A2, 23.8 GHZ
BEAM POS. 30, CROSSTRACK PLANE
DATAFILE (S): AH291

DATE: 1 Jun 1998




METSAT 2 A2, 23.8 GHZ
BEAM POS. 30, DOWNTRACK PLANE
DATAFILE (S): AH295

DATE: 1 Jun 1998




METSAT 2 A2, 23.8 GHZ
COLD CAL. POS., CROSSTRACK PLANE
DATAFILE (S): AH323

DATE: 2 Jun 1998




METSAT 2 A2, 23.8 GHZ
COLD CAL. POS., DOWNTRACK PLANE
DATAFILE (S): AH325

DATE: 2 Jun 1998




METSAT 2 A2, 31.4 GHZ
BEAM POS. 1, CROSSTRACK PLANE
DATAFILE (S): AH315

DATE: 2 Jun 1998




METSAT 2 A2, 31.4 GHZ
BEAM POS. 1, DOWNTRACK PLANE
DATAFILE (S): AH319

DATE: 2 Jun 1998




METSAT 2 A2, 31.4 GHZ
BEAM POS. 15, CROSSTRACK PLANE
DATAFILE (S): AH307

DATE: 1 Jun 1998




METSAT 2 A2, 31.4 GHZ
BEAM POS. 15, DOWNTRACK PLANE
DATAFILE (S): AH311

DATE: 1 Jun 1998




METSAT 2 A2, 31.4 GHZ
BEAM POS. 30, CROSSTRACK PLANE
DATAFILE (S): AH299

DATE: 1 Jun 1998



METSAT 2 A2, 31.4 GHZ
BEAM POS. 30, DOWNTRACK PLANE
DATAFILE (S): AH303

DATE: 1 Jun 1998

 NASA National Aeronautics and Space Administration				Report Documentation Page			
1. Report No. ---		2. Government Accession No. ---		3. Recipient's Catalog No. ---			
4. Title and Subtitle Integrated Advanced Microwave Sounding Unit-A (AMSU-A), Performance Verification Report				5. Report Date June 1998			
				6. Performing Organization Code ---			
7. Author(s) B. Brest				8. Performing Organization Report No. 11157			
				10. Work Unit No. ---			
9. Performing Organization Name and Address Aerojet 1100 W. Hollyvale Azusa, CA 91702				11. Contract or Grant No. NAS 5-32314			
				13. Type of Report and Period Covered Final			
12. Sponsoring Agency Name and Address NASA Goddard Space Flight Center Greenbelt, Maryland 20771				14. Sponsoring Agency Code ---			
15. Supplementary Notes ---							
16. ABSTRACT (Maximum 200 words) This is the Performance Verification Report, METSAT 3 A2 Assy, S/N 107, AMSU-A2 Antenna Assy, P/N 1331210-3-SPN, S/N 03 for the Integrated Advanced Microwave Sounding Unit-A (AMSU-A).							
17. Key Words (Suggested by Author(s)) EOS Microwave System			18. Distribution Statement Unclassified --- Unlimited				
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of pages ---			
				22. Price ---			

NASA FORM 1626 OCT 86

PREPARATION OF THE REPORT DOCUMENTATION PAGE

The last page of a report facing the third cover is the Report Documentation Page, RDP. Information presented on this page is used in announcing and cataloging reports as well as preparing the cover and title page. Thus, it is important that the information be correct. Instructions for filling in each block of the form are as follows:

Block 1. Report No. NASA report series number, if preassigned.

Block 2. Government Accession No. Leave blank.

Block 3. Recipient's Catalog No. Reserved for use by each report recipient.

Block 4. Title and Subtitle. Typed in caps and lower case with dash or period separating subtitle from title.

Block 5. Report Date. Approximate month and year the report will be published.

Block 6. Performing Organization Code . Leave blank.

Block 7. Authors. Provide full names exactly as they are to appear on the title page. If applicable, the word editor should follow a name.

Block 8. Performing Organization Report No. NASA installation report control number and, if desired, the non-NASA performing organization report control number.

Block 9. Performing Organization Name and Address. Provide affiliation (NASA program office, NASA installation, or contractor name) of authors.

Block 10. Work Unit No. Provide Research and Technology Objectives and Plants (RTOP) number.

Block 11. Contract or Grant No. Provide when applicable.

Block 12. Sponsoring Agency Name and Address. National Aeronautics and Space Administration, Washington, D.C. 20546-0001. If contractor report, add NASA installation or HQ program office.

Block 13. Type of Report and Period Covered. NASA formal report series; for Contractor Report also list type (interim, final) and period covered when applicable.

Block 14. Sponsoring Agency Code. Leave blank.

Block 15. Supplementary Notes. Information not included

elsewhere: affiliation of authors if additional space is required for Block 9, notice of work sponsored by another agency, monitor of contract, information about supplements (file, data tapes, etc.) meeting site and date for presented papers, journal to which an article has been submitted, note of a report made from a thesis, appendix by author other than shown in Block 7.

Block 16. Abstract. The abstract should be informative rather than descriptive and should state the objectives of the investigation, the methods employed (e.g., simulation, experiment, or remote sensing), the results obtained, and the conclusions reached.

Block 17. Key Words. Identifying words or phrases to be used in cataloging the report.

Block 18. Distribution Statement. Indicate whether report is available to public or not. If not to be controlled, use "Unclassified-Unlimited." If controlled availability is required, list the category approved on the Document Availability Authorization Form (see NHB 2200.2, Form FF427). Also specify subject category (see "Table of Contents" in a current issue of STAR) in which report is to be distributed.

Block 19. Security Classification (of the report). Self-explanatory.

Block 20. Security Classification (of this page). Self-explanatory.

Block 21. No. of Pages. Count front matter pages beginning with iii, text pages including internal blank pages, and the RDP, but not the title page or the back of the title page.

Block 22. Price Code. If Block 18 shows "Unclassified-Unlimited," provide the NTIS price code (see "NTIS Price Schedules" in a current issue of STAR) and at the bottom of the form add either "For sale by the National Technical Information Service, Springfield, VA 22161-2171" or "For sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402-0001," whichever is appropriate.

REPORT DOCUMENTATION PAGE			<i>Form Approved OMB No. 0704-0188</i>	
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</small>				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE		3. REPORT TYPE AND DATES COVERED
4. TITLE AND SUBTITLE Integrated Advanced Microwave Sounding Unit-A (AMSU-A), Performance Verification Report			5. FUNDING NUMBERS NAS 5-32314	
6. AUTHOR(S) D. Brest				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Aerojet 1100 W. Hollyvale Azusa, CA 91702			8. PERFORMING ORGANIZATION REPORT NUMBER 11157 June 1998	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) NASA Goddard Space Flight Center Greenbelt, Maryland 20771			10. SPONSORING/MONITORING AGENCY REPORT NUMBER ---	
11. SUPPLEMENTARY NOTES ---				
12a. DISTRIBUTION/AVAILABILITY STATEMENT ---			12b. DISTRIBUTION CODE ---	
13. ABSTRACT (Maximum 200 words) This is the Performance Verification Report, METSAT 3 A2 Assy, S/N 107, AMSU-A2 Antenna Assy, P/N 1331210-3-SPN, S/N 03 for the Integrated Advanced Microwave Sounding Unit-A (AMSU-A).				
14. SUBJECT TERMS EOS Microwave System			15. NUMBER OF PAGES 16. PRICE CODE ---	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR	

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filing in each block of the form follow. It is important to stay within the lines to meet optical scanning requirements.

Block 1. Agency Use Only (Leave blank)

Block 2. Report Date Full publication date including day, month, and year, if available (e.g., 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g., 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume report the primary title, add volume number and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C	-	Contract	PR	-	Project
G	-	Grant	TA	-	Task
PE	-	Program Element	WU	-	Work Unit Accession No.

Block 6. Author(s) Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es) Self-explanatory.

Block 8. Performing Organization Report Number Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es) Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Reports Number (if known).

Block 11. Supplementary Notes Enter information not included elsewhere such as: Prepared in cooperation with ...; Trans. of ...; To be published in ... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12.a Distribution/Availability Statement Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g., NOFORN, REL, ITAR).

DOD - See DoDD 5230.24 *Distribution Statement on Technical Documents*

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12.b Distribution Code

DOD - Leave blank.

DOE - Enter DOE distribution categories from the standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract Include a brief *Maximum 200 words* factual summary of the most significant information contained in the report.

Block 14. Subject Terms Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages Enter the total number of pages.

Block 16. Price Code Enter appropriate price code (NTIS only).

Block 17 - 19. Security Classifications Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.



DOCUMENT APPROVAL SHEET

TITLE Performance Verification Report, METSAT 3 A2 Assembly, Serial No. 107 AMSU-A2 Antenna Assembly, P/N 1331210-3-SPN, S/N 03		DOCUMENT NO. Report 11157 June 1998	
INPUT FROM: D. Brest	DATE	CDRL: 208	SPECIFICATION ENGINEER: DATE
CHECKED BY:	DATE	JOB NUMBER:	DATE
APPROVED SIGNATURES		DEPT. NO.	DATE
Engineer (D. Brest) <u>[Signature]</u>		8721	6/9/98
Product Team Leader (J. Alvarez) <u>[Signature]</u>		8621	6/9/98
Systems Engineer (R. Platt) <u>[Signature]</u>		8311	6/9/98
Quality Assurance (R. Taylor) <u>[Signature]</u> <u>FOR</u>		7831	6/10/98
Technical Director/PMO (R. Hauerwaas) <u>[Signature]</u>		4001	6/10/98
Configuration Management (J. Cavanaugh) <u>[Signature]</u>		8361	6/10/98
By my signature, I certify the above document has been reviewed by me and concurs with the technical requirements related to my area of responsibility.			
RELEASE (Data Center) _____ _____			
Please return this sheet and the reproducible master to Jim Kirk (Bldg. 1/Dept. 8631), ext. 2081.			